

Quality Passport No. 12159/649

Turkmenbashy c.

Analysis 9510 since 30.03.2021

Oil product: diesel fuel Eco 5 sort ABC

Storage tank No 46 Measured(cm)8860 Cistern

TS 05766698-88-2019

indicators	norm	fact
Cetane index, no less than	46,0	53
Density at 15kg/m ³	820-845	835,0
Density at 20kg/m ³		831,5
Polycyclic aromatic hydrocarbon %, by mass,' no more than	8	temporarily undefined
Sulphur content 1 O'6 no more	0,001(10)	5,59
Temperature of explosion in a closed crucible, Celsius no more than	55,0	5,59 70
Coking 10% of residue %/by mass/no more than	0,3	0,01
Ash content %/by mass/no more than	0,01	absent
Water content 10 ¹⁶ no more than	0,02(200)	68
Content of mechanical mixtures JO" ⁶ no more than	24	absent
Copper plate corrosion/3h at 50°, Celsius	withstands	withstands
Oxidation capacity -total amount of sediment g/m3	25,0	temporarily undefined
Lubricity -adjustment, diameter wear patch 60 Celsius, micron no more than	460	402
Kinematic viscosity at 40 Celsius mm/s	2,00-4,50	2,747
Fractional composition of 95% distilled at a temperature Celsius, no higher than Critical filterability temperature	340 Clarifying grading	334
Celsius, no more than	A B C D E F	
	5 0 -5 -10 -15 -20	-7